



Product Information 02.40.10

04-02-2023

Agrifluid HT

Description

Agrifluid HT is a modern, universal hydraulic and transmission oil. It is based on solvent-refined base oils, combined with additives. Agrifluid HT features the following properties:

- A very high and stable viscosity index
- A very low pour point
- Excellent oxidation stability
- Effective 'Extreme Pressure' and wear resistance
- Suitable for systems with wet brakes
- Outstanding resistance to rust and corrosion

Application

Agrifluid HT is a UTTO (Universal Tractor Transmission Oil), developed specially for everyday operating conditions in the agricultural industry. This universal oil has been developed as a lubricant oil for the hydraulic and transmission systems of the most common agricultural and earth-moving machines.

Specifications

API GL-4

Allison C4

Case MS1206 / MS1207 / MS1209

Cat TO-2

Ford M2C134-D

John Deere J20C

Massey Ferguson M1135 / M1143

NH 410B

Volvo WB 101 (97303)

ZF TE-ML 03E / 05F / 06K

Typicals

Density at 15 °C, kg/l	0,881
Viscosity -25 °C, mPa.s	6120
Viscosity -20 °C, mPa.s	3020
Viscosity 40 °C, mm ² /s	62,6
Viscosity 100 °C, mm ² /s	10,60
Viscosity Index	155
Flash Point COC, °C	225
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,3
Sulphate Ash, %	1,19

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings

34223
5 L can



32735
20 L Bag in
Box



36090
20 L pail



11176
60 L drum



11276
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.