



Product Information 08.60.35

17-05-2025

Abacot MEP HD 220

Description

Abacot MEP HD 220 is a fully synthetic transmission oil based on premium polyalphaolefin (PAO) base oils. It is supplemented with special additives to achieve the following properties:

- Naturally high viscosity index
- Excellent high- and low-temperature properties
- Excellent resistance to high pressures and shock loads
- Effective protection against micro pitting
- Very high resistance to corrosion and oxidation
- Long service life
- Substantial reduction in friction losses

Application

Abacot MEP HD 220 is particularly suitable for the lubrication of heavy-duty mechanical transmissions and bearing systems with a high thermal load. Compared with mineral transmission oil, the oil change interval can be significantly extended. This oil can easily be mixed with mineral transmission oil, meaning that switching from mineral transmission oil to Abacot MEP HD 220 does not require a specialised procedure.

Specifications

AGMA 9005-F16 (AS)

AIST (US Steel) 224

David Brown S1.53.106

DIN 51517-3 CLP

Flender

ISO 12925-1 Type CKD

Typicals

Colour	1.0
Density at 15 °C, kg/l	0,857
Viscosity 40 °C, mm ² /s	220,00
Viscosity 100 °C, mm ² /s	29,10
Viscosity Index	172
Flash Point PM, °C	205
Flash Point COC, °C	258
Pour Point, °C	-45
Acid number, mgKOH/g	0,61

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



34581
20 L pail



37964
20 L can



34842
60 L drum



34306
200 L drum



32059
208 L drum



37644
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.