

Product Information 09.10.01

05-12-2021

Kroon-Oil Coolant -26

Description

Coolant -26 is a classic coolant, based on monoethylene glycol and softened water. It is supplemented with additives to achieve the following properties:

- Effective protection of all metals that are used in the engine and cooling system
- Does not affect gaskets and hoses
- Good resistance to foaming
- Protection of aluminium cylinder heads

Application

Coolant -26 can be used throughout the year in the cooling systems of petrol and diesel engines. Coolant -26 should be used undiluted and will then provide protection down to -26 °C.

Specifications

BS 6580:2010

Typicals

Colour	BLAUW
Density at 15 °C, kg/l	1,046
pH - value	8,2
Reserve alkalinity, ml	8,3
Crystallizationpoint, °C	-26

Available packagings



04203
1 L bottle



04302
5 L can



14004
20 L can



14103
60 L drum



14203
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.