

Product Information 01.30.22 03-05-2024

Torsynth 5W-40

Description

Torsynth 5W-40 is a modern, fuel-saving, universal motor oil based on synthetic base oils that have a naturally high viscosity index. It is supplemented with carefully balanced additives to achieve the following properties:

- Fuel saving (up to 2%)
- A very high viscosity index and high resistance to shearing
- A smooth cold start
- A protective lubricant film at high temperatures
- Excellent dispersion and detergency, thereby preventing a high build-up of black sludge
- Very high resistance to wear, corrosion and foaming
- Suitable for use in motor vehicles with the latest catalytic converter technologies

Application

Torsynth 5W-40 is a universal fuel-saving motor oil, suitable for all petrol and diesel engines, both with and without turbochargers, in cars and vans. Consult the product specifications in the product sheet for correct usage.

Specifications

Suitable for use:
ACEA A3/B4
API SN/CF
BMW Longlife-01
Fiat 9.55535-M2
GM LL-B-025
MB 229.3 / 226.5
PSA B71 2296
Renault RN0700 / RN0710
VW 502.00 / 505.00

Typicals

Density at 15 °C, kg/l	0,856
Viscosity -30 °C, mPa.s	5970
Viscosity 40 °C, mm²/s	83,90
Viscosity 100 °C, mm²/s	13,90
Viscosity Index	173
Flash Point COC, °C	230
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,8
Sulphate Ash, %	1,33

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings

34446 1 L bottle

36169 4 L can

34447 5 L can



37482 15 L Bag in

Box



32639 20 L Bag in Box



34448

20 L pail

32246

20 L can



34449

60 L drum



34450 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.