



## Product Information 01.70.50

04-07-2022

### Classic Multigrade 20W-50

#### Description

Classic Multigrade 20W-50 is a mineral SAE 20W-50 multigrade motor oil for classic petrol and diesel engines. Premium mineral base oils plus carefully selected additives provide Classic Multigrade 20W-50 with the following properties:

- Outstanding lubrication properties
- Superb protection against wear
- A stable and high viscosity index suitable for use in all seasons
- Effective protection against corrosion
- Does not cause caked-on dirt to become detached
- Excellent resistance to foaming
- Fully compatible with classic seals and rubber

#### Application

Classic Multigrade 20W-50 is a premium, mineral multigrade motor oil for classic petrol engines and classic diesel engines in cars and vans. Classic Multigrade 20W-50 is ideal for use in classic cars from the 1960s, 1970s, and early 1980s that require SAE 20W-50 motor oil.

#### Specifications

API SF/CC

CCMC G2/D1

MIL-L-46152 B/C

Ford M2C153-C (SF/CC)

Ford M2C9011-A

GM 6085M

GM 6041M

GM 6136M

#### Typicals

Density at 15 °C, kg/l 0,886

Viscosity -15 °C, mPa.s 7940

Viscosity 40 °C, mm<sup>2</sup>/s 159,00

Viscosity 100 °C, mm<sup>2</sup>/s 17,30

Viscosity Index 117

Flash Point COC, °C 244

Pour Point, °C -24

Total Base Number, mgKOH/g 3,5

Sulphate Ash, % 0,86

HTHS, mPa.s 4,56

Noack, % 7,5

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



**Available packagings**



34538  
1 L tin



36699  
5 L tin



34612  
60 L drum



35382  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.