

## Product Information 01.70.55

21-02-2019

### Classic Racing Oil 15W-50

#### Description

Classic Racing Oil 15W-50 is premium, semi-synthetic motor oil specially developed for use in classic motor racing. A combination of synthetic and quality mineral base oils and carefully selected additives provide Classic Racing Oil 15W-50 with the following properties:

- Outstanding lubrication properties, even at very high operating temperatures
- High viscosity index
- Very effective shear stability
- Outstanding protection against wear, even under extreme conditions
- Ensures stable oil pressure
- Outstanding detergency and dispersion
- High resistance to corrosion and foaming

#### Application

Classic Racing Oil 15W-50 is a premium, semi-synthetic multigrade motor oil, specially developed for high to very high-powered classic combustion engines. This makes Classic Racing Oil 15W-50 ideally suited for use in classic car engines specially prepared for participation in classic motorsports events. Classic Racing Oil 15W-50 is also highly suitable for use in the overhauled engines of high-powered, post-war classic sports cars.

#### Specifications

API SL/CF

#### Typicals

Density at 15 °C, kg/l	0,870
Viscosity -20 °C, mPa.s	6800
Viscosity 40 °C, mm <sup>2</sup> /s	131,00
Viscosity 100 °C, mm <sup>2</sup> /s	17,30
Viscosity Index	143
Flash Point COC, °C	226
Pour Point, °C	-27
Total Base Number, mgKOH/g	8,0
Acid number, mgKOH/g	2,58
Sulphate Ash, %	1,02
Noack, %	9,8

#### Available packagings



34539  
1 L tin



35422  
20 L can



34591  
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.