

## Product Information 01.70.30

04-12-2023

### Preservative Monograde 30

#### Description

Preservative Monograde 30 is a special motor oil for preserving combustion engines that are being placed in long-term storage. For example, it is perfect for the winter storage of vehicles including classic cars, motorcycles or pleasure boats. Premium mineral base oils, carefully selected additives and special Vapour Phase Corrosion Inhibitors provide Preservative Monograde 30 with the following properties:

- Outstanding corrosion protection to all internal engine parts during long-term storage
- Excellent detergency and dispersion
- Outstanding resistance to oxidation
- Good resistance to wear and foaming

#### Application

Preservative Monograde 30 protects combustion engines from corrosion during long-term storage. Suitable for short-term use as an ordinary motor oil – the vehicle or vessel can be driven or sailed under its own power without problems.

Instructions for use:

- Change the used motor oil while the engine is at operating temperature.
- Fit a new oil filter
- Allow the engine to idle for a few minutes, before placing in storage. Replace with the recommended motor oil once the storage period is over.

#### Specifications

MIL-L-21260D

#### Typicals

Density at 15 °C, kg/l	0,885
Viscosity 40 °C, mm <sup>2</sup> /s	103,00
Viscosity 100 °C, mm <sup>2</sup> /s	11,70
Viscosity Index	98
Flash Point COC, °C	230
Pour Point, °C	-18
Total Base Number, mgKOH/g	3,6
Sulphate Ash, %	0,55

#### Available packagings



34541  
1 L tin

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.