

Product Information 09.10.18

27-07-2024

Kroon-Oil Welding Fluid

Description

Welding Fluid is a special coolant for welding equipment equipped with liquid cooling. The product is based on 1.2 ethanediol and specially softened water. It is supplemented with carefully balanced additives to achieve the following unique properties:

- Does not affect seals and hoses
- Provides the metal parts on the welding equipment with outstanding protection against corrosion
- Very high resistance to foaming
- Thanks to the high viscosity, the head of the welding gun is kept sufficiently cool
- Good lubricating properties in order to lubricate the pump
- Outstanding heat transfer properties
- Fluid is free of lumps and/or crystallisation

Application

Welding Fluid is a special coolant for use in welding equipment with a cooling system. Welding Fluid should be used undiluted, and will then provide frost protection down to -26 °C.

Typicals

Density at 15 °C, kg/l	1,068
pH - value	8,6
Reserve alkalinity, pH	8,0
Crystallizationpoint, °C	-26

Available packagings



04320
5 L can



32981
20 L can



14215
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.