

Product Information 01.10.40

05-12-2023

Flushing Oil

Description

Flushing Oil is an effective single-grade, high quality flushing oil. The advantageous choice of viscosity, premium solvent-refined base oils and specially detergent and dispersion additives make Flushing Oil extremely effective. Thanks to the perfect formulation of these substances, the product provides the following properties:

- High dispersion and detergency
- Can also be used effectively used at low temperatures
- High resistance to wear, corrosion and foaming
- Significant resistance to oxidation
- Can be easily and effectively mixed with both multigrade mineral and (fully) synthetic motor oils.
- Has completely no effect on (old) gaskets and seals: no risk of leakage
- Good moisture absorber and neutraliser

Application

Flushing Oil is a flushing oil for petrol and diesel engines. It works effectively in the switch from a lower quality to improved quality product. It is also highly suitable if the motor oil contains a lot of condensed water, coolants, fuel dilution and/or white sludge.

Instructions for use:

- Allow the engine to idle for 20-30 minutes (preferably when engine is warm)
- Then drain off, replace the oil filter and fill the engine with Kroon-Oil (fully) synthetic motor oil.

Specifications

API SF/CC

Typicals

Density at 15 °C, kg/l	0,886
Viscosity -15 °C, mPa.s	5000
Viscosity 40 °C, mm ² /s	68,00
Viscosity 100 °C, mm ² /s	8,00
Viscosity Index	98
Flash Point COC, °C	215
Pour Point, °C	-24
Total Base Number, mgKOH/g	3,5
Sulphate Ash, %	0,55

Available packagings



34543

1 L tin

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.