

Product Information 02.60.15

21-02-2019

Classic Gear EP 80

Description

Classic Gear EP 80 is a medium SAE 80 transmission oil with extreme pressure protection for use in classic transmissions. The standards that modern lubricants are required to meet mean that modern-day transmission oils are often of low viscosity and are significantly less suitable, or unsuitable, for use in the transmissions of classic vehicles. In order to lubricate precious and often valuable classic cars safely, Kroon-Oil has developed a range of Classic Oils that are tailor-made for use in classic vehicles. Premium mineral base oils and carefully selected additives provide Classic Gear EP 80 with the following properties:

- Outstanding lubrication properties
- Good resistance to corrosion
- Good EP properties
- Compatible with classic seals and rubbers
- Good resistance to foaming

Application

Classic Gear EP 80 is a mineral SAE 80 transmission oil. The product is suitable for use in manual transmissions and other transmissions in classic vehicles that require a medium single-grade oil with extreme pressure protection that meets the API GL-4 specification.

Specifications

API GL-4

Mil-L-2105

MB 235.1

Typicals

Density at 15 °C, kg/l	0,879
Viscosity 40 °C, mm ² /s	77,00
Viscosity 100 °C, mm ² /s	9,50
Viscosity Index	98
Flash Point COC, °C	205
Pour Point, °C	-36
Brookfield -26°C, mPa.s	62400

Available packagings



34546

1 L tin

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.