

Product Information 02.60.20

03-07-2025

Classic Gear LS 90

Description

Classic Gear LS 90 is a limited slip hypoid SAE 90 transmission oil for classic vehicles. Modern and often low-viscosity transmission oils are significantly less suitable, or unsuitable, for use in classic transmissions. Kroon-Oil Classic Oils line is tailor-made for use in classic vehicles. Premium mineral base oils and carefully selected additives provide Classic Gear LS 90 with the following properties:

- Outstanding lubrication properties
- Excellent limited slip properties: extremely well-suited for use in locking differentials
- Good resistance to corrosion
- Outstanding EP properties
- Excellent protection against wear, even in the case of heavy shock loads
- Compatible with classic seals and rubbers
- Good resistance to foaming

Application

Classic Gear LS 90 is a special, limited slip hypoid transmission oil. The product is suitable for locking differentials and other transmissions in classic vehicles that require limited-slip transmission oil that meets the API GL-5 specification.

Specifications

API GL-5 Limited Slip

MIL-L-2105B/C

Ford M2C 104-A

GM 1942380

ZF TE-ML 05C, 05N, 21N

Typicals

Density at 15 °C, kg/l	0,877
Viscosity 40 °C, mm ² /s	120,00
Viscosity 100 °C, mm ² /s	15,00
Viscosity Index	125
Flash Point COC, °C	214
Pour Point, °C	-36
Total Base Number, mgKOH/g	2,0
Acid number, mgKOH/g	1,27
Brookfield -26°C, mPa.s	40700
Calcium, mg/kg	240
Zinc, mg/kg	0

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



34548

1 L tin

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.