

Product Information 01.70.45

24-10-2021

Classic Multigrade 15W-40

Description

Classic Multigrade 15W-40 is a mineral SAE 15W-40 multigrade motor oil for classic petrol and diesel engines. Premium mineral base oils plus carefully selected additives provide Classic Multigrade 15W-40 with the following properties:

- Outstanding lubrication properties
- Superb protection against wear
- A stable and high viscosity index suitable for use in all seasons
- Effective protection against corrosion
- Does not cause caked-on dirt to become detached
- Excellent resistance to foaming
- Fully compatible with classic seals and rubbers

Application

Classic Multigrade 15W-40 is a premium, mineral multigrade motor oil for classic petrol engines and classic diesel engines in cars and vans. Classic Multigrade 15W-40 is ideal for use in classic cars from the 1960s, 1970s, and early 1980s which require SAE 15W-40 motor oil.

Specifications

API SF/CC

CCMC G2/D1

MIL-L-46152 B/C

Ford M2C153-C (SF/CC)

Ford M2C9011-A

GM 6085M

GM 6041M

GM 6136M

Typicals

Density at 15 °C, kg/l 0,883

Viscosity -20 °C, mPa.s 6300

Viscosity 40 °C, mm²/s 103,40

Viscosity 100 °C, mm²/s 14,00

Viscosity Index 137

Flash Point COC, °C 232

Pour Point, °C -30

Total Base Number, mgKOH/g 3,5

Sulphate Ash, % 0,86

Noack, % 11,7

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



34537
1 L tin



34611
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.