

## Product Information 09.10.09

04-02-2023

### Kroon-Oil Coolant SP 13

#### Description

Coolant SP 13 is a premium, ready-to-use, Long Life coolant with frost protection down to -38 °C, which contains the patented LOBRID additive technology based on 'Organic Acid Technology' and a small percentage of silicate. It has been specifically designed for use in engines/radiators made from light metals such as aluminium, magnesium or their alloys and complies with VW specification TL VW 774J (G13).

Thanks to the addition of powerful corrosion inhibitors, the product is practically unaffected by ageing. Corrosion inhibitors also prevent sludge and deposits forming in the radiator, thereby also ensuring optimal cooling in the long term.

Please note! Reliable measurement of the freeze protection level is only possible using special refractometers with a separate G13 scale!

#### Application

Coolant SP 13 is a purple-coloured, ready-to-use coolant for the cooling systems of Volkswagen, Audi, Skoda and Seat vehicles. Coolant SP 13 can be easily mixed with Kroon-Oil Coolant SP 12++ and Kroon-Oil Coolant SP 12. Optimal results can only be achieved with 100% filling.

#### Specifications

VW TL 774-J (G13)

#### Typicals

|                          |       |
|--------------------------|-------|
| Density at 15 °C, kg/l   | 1,088 |
| pH - value               | 8,3   |
| Crystallizationpoint, °C | -38   |

#### Available packagings



34685  
1 L bottle



34686  
5 L can



34687  
20 L can



34688  
60 L drum



34689  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.