



Product Information 01.50.13

21-02-2019

Agrisynth LSP 10W-40

Description

Agrisynth LSP 10W-40 is a very high-quality, synthetic motor oil specially developed for the latest generation of heavy-duty diesel engines in tractors and earth-moving machinery. Special Low SAPS additives technology, combined with top-quality base oils, ensures that this premium product provides the following benefits:

- A low sulfate ash, phosphorus and sulfur content, which makes this product suitable for use in engines fitted with an exhaust gas after-treatment device
- Reduced fuel consumption
- Excellent cleaning ability, as a result of which deposits, sludge and particle formation are kept to a minimum
- Superb protection against wear
- Excellent resistance to oxidation and corrosion

Application

Agrisynth LSP 10W-40 is a premium Low SAPS motor oil suitable for use in the latest generation of diesel engines in agricultural vehicles and earth-moving machinery. Particularly suitable for use in clean Tier IIIb and Tier IIIa engines, whether or not equipped with an exhaust gas after-treatment device (particulate filter and/or SCR catalytic converter) and/or an EGR system. If the manufacturer so specifies, longer oil change intervals may be applied.

Specifications

ACEA E6, E7

API CI-4

Volvo VDS-3

Mack EO-N, Renault VI RLD-2

MB-Approval 228.51

MAN M 3477/M 3271-1

Deutz DQC IV-10 LA

DAF Long Drain

Renault VI RXD/RGD

MTU Type 3.1

JASO DH-2

Cummins CES 20076/20077

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,863
Viscosity -25 °C, mPa.s	6120
Viscosity 40 °C, mm ² /s	95,90
Viscosity 100 °C, mm ² /s	14,30
Viscosity Index	154
Flash Point PM, °C	203
Flash Point COC, °C	222
Pour Point, °C	-39
Total Base Number, mgKOH/g	10,1

Available packagings



34739
20 L pail



32294
20 L can



34740
60 L drum



34741
208 L drum



32647
999 L IBC