

# **Product Information 08.50.07 17-05-2025**

## **Kroon-Oil Paraflo 15**

### Description

Paraflo 15 is a white, technical mineral oil. The product is mainly made up of a mixture of saturated paraffin and cycloparaffin hydrocarbons. As a result of intensive refining, this oil is acid-free and almost colour and odour-free.

# **Application**

Paraflo 15 is used:

- · As a lubricant for precision engineering equipment and for sewing machines and other textile machines
- As a raw material for various processes PLEASE NOTE! This oil should not be used in the medical and food industries, in which food products may come into contact with the oil.

#### **Typicals**

Density at 15 °C, kg/l	0,852
Viscosity 20 °C, mm²/s	37,50
Viscosity 40 °C, mm²/s	15,60
Viscosity 100 °C, mm <sup>2</sup> /s	3,60
Viscosity Index	114
Flash Point PM, °C	183
Flash Point COC, °C	192
Pour Point, °C	-21

## **Available packagings**



02216

1 L bottle















37000 35 20 L pail 20

35418 20 L can

60 L drum

200 L drum

12240 208 L drum

34804 1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.