

Product Information 01.70.20

27-04-2024

Classic Monograde 50

Description

Classic Monograde 50 is a mineral, single-grade SAE 50 motor oil specially designed for classic petrol and diesel engines. Carefully selected additives provide the product with the following properties:

- Outstanding lubrication properties
- Superb protection against wear
- Effective protection against corrosion
- Does not cause caked-on dirt to become detached
- Excellent resistance to foaming
- Fully compatible with classic seals and rubbers

Application

Classic Monograde 50 is a mineral motor oil for classic combustion engines: modern motor oils can have a disastrous effect on such engines. In order to lubricate precious and often valuable classic cars safely, Kroon-Oil has developed its Classic Oils. This is a complete range that has been specially developed for use in classic vehicles. Classic Monograde 50 is suitable for post-war classic petrol and diesel engines that require a lightly to moderately enhanced single-grade motor oil.

Specifications

API SF/CC

CCMC G2/D1

MIL-L-46152B/C

Ford M2C153-C (SF/CC)

Ford M2C9011-A

GM 6085M

Typicals

Density at 15 °C, kg/l	0,899
Viscosity 40 °C, mm ² /s	240,00
Viscosity 100 °C, mm ² /s	18,80
Viscosity Index	96
Flash Point COC, °C	258
Pour Point, °C	-12
Total Base Number, mgKOH/g	3,5
Acid number, mgKOH/g	2,25
Sulphate Ash, %	0,55

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



34535
1 L tin



34789
60 L drum



34966
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.