



## Product Information 01.20.64

05-12-2021

### Agri Diesel MSP 15W-40

#### Description

AgriDiesel MSP 15W-40 is a premium, mineral motor oil specially developed for the latest generation of heavy-duty diesel engines in tractors and earth-moving machinery. Special Mid SAPS additive technology, combined with top-quality base oils, ensures that this product provides the following benefits:

- A low sulfate ash, phosphorus and sulfur content, which makes this product suitable for use in engines fitted with an exhaust gas after-treatment device
- Excellent cleaning ability, as a result of which deposits, sludge and particle formation are kept to a minimum
- Superb protection against wear
- Excellent resistance to oxidation and corrosion

#### Application

AgriDiesel MSP 15W-40 is a high-grade Mid SAPS motor oil suitable for use in the latest generation of diesel engines in agricultural vehicles and earth-moving machinery. Particularly suitable for use in clean Tier IIIb and Tier IIIa engines, whether or not equipped with an exhaust gas after-treatment device (particulate filter and/or SCR catalytic converter) and/or an EGR system. If the manufacturer so specifies, longer oil change intervals may be applied.

#### Specifications

ACEA E9

API CK-4/SN

Mack EOS-4.5

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

Deutz DQC III-18 LA

Ford WSS M2C171-F1

MAN M 3775

MB 228.31

MTU Type 2.1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

### Typicals

Density at 15 °C, kg/l	0,874
Viscosity -20 °C, mPa.s	4860
Viscosity 40 °C, mm <sup>2</sup> /s	99,90
Viscosity 100 °C, mm <sup>2</sup> /s	13,90
Viscosity Index	140
Flash Point COC, °C	222
Pour Point, °C	-36
Total Base Number, mgKOH/g	8,1
Acid number, mgKOH/g	0,00
Sulphate Ash, %	0,90
Noack, %	8,8

### Available packagings



35081  
5 L can



32721  
20 L Bag in  
Box



34969  
20 L pail



34970  
60 L drum



34971  
208 L drum