

## Product Information 01.10.20

05-12-2021

### Motor Oil HDX 10W

#### Description

HDX 10W is a single-grade motor oil based on premium solvent-refined base oils with additives to achieve the following properties:

- High resistance to wear, corrosion and foaming

#### Application

HDX 10W is a lubricant oil suitable for petrol engines along with diesel engines for cars and vans working under light conditions. Not suitable for turbo diesels that require a minimum of an API CD or Mil-L-2104 C/D level.

#### Specifications

API SF/CC

CCMC G2/D1

MIL-L-46152B/C

Ford M2C153-C (SF/CC)

Ford M2C9011-A

GM 6085M

#### Typicals

Density at 15 °C, kg/l	0,870
Viscosity -25 °C, mPa.s	3850
Viscosity -20 °C, mPa.s	3000
Viscosity 40 °C, mm <sup>2</sup> /s	38,20
Viscosity 100 °C, mm <sup>2</sup> /s	5,60
Viscosity Index	98
Flash Point COC, °C	205
Pour Point, °C	-30
Total Base Number, mgKOH/g	3,5
Sulphate Ash, %	0,55

#### Available packagings



35042  
20 L pail



10070  
20 L can



10105  
60 L drum



10205  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.