



Product Information 01.30.52

17-04-2024

Armado Synth NF 10W-40

Description

Armado Synth NF 10W-40 is an extremely modern synthetic diesel motor oil for use in commercial vehicles that is of an unprecedented level of quality. By using synthetic base oils combined with the latest additives technology, Armado Synth NF 10W-40 sets the new standard for motor oil used in commercial vehicles. The product achieves the following properties:

- Saves fuel and keeps oil consumption exceptionally low
- A smooth cold start, even at extremely low temperatures
- Provides a strong lubricant film, even under the most extreme operating conditions
- Excellent cleaning ability
- Prevents engine wear
- Copes exceptionally well with the long oil change intervals that are common today
- Also prevents bore polishing

Application

Armado Synth NF 10W-40 is suitable for modern diesel engines that are required to perform in the most severe operating conditions. Highly suitable for use in diesel engines with low exhaust gas emissions (including EURO 3, 4 and 5), in combination with diesel fuels with a low sulfur content. Armado Synth NF 10W-40 has been developed, in keeping with the manufacturers' instructions, to allow very long oil change intervals (100,000+ km) while retaining a very long and problem-free service life.

Specifications

ACEA E4, E7

API CF

MAN M 3277

DTFR 15B120 (228.5)

MB 228.5

Scania LDF-3

Mack EO-N

Renault VI RLD-2

Volvo VDS-3

Deutz DQC III-10

MB 228.5

MTU Type 3

Scania LDF-2

DAF Extended Drain

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,863
Viscosity -25 °C, mPa.s	5480
Viscosity 40 °C, mm ² /s	85,60
Viscosity 100 °C, mm ² /s	13,00
Viscosity Index	152
Flash Point COC, °C	228
Pour Point, °C	-36
Total Base Number, mgKOH/g	15,9
Sulphate Ash, %	1,80

Available packagings



35069
20 L can