



Product Information 01.50.10

26-10-2021

Kroontrak Super 10W-30

Description

Kroontrak Super 10W-30 is a modern multifunctional oil for use in agricultural and earth-moving machinery. The product is based on premium solvent-refined base oils with additives to achieve the following properties:

- Powerful dispersion and detergency
- High resistance to wear, corrosion and foaming
- Very high resistance to oxidation
- Excellent EP properties
- A high and stable viscosity index

Application

Kroontrak Super 10W-30 has been specially developed for everyday operating conditions in agriculture. The universal, multifunctional oil is what is known as an STOU: Super Tractor Oil Universal. It is therefore suitable for use as an all-purpose lubricant for:

- Petrol engines
- Diesel engines and turbo diesels
- Transmissions, also for wet brakes
- Hydraulic systems

Specifications

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D

Ford M2C159-C

John Deere J27

Massey Ferguson CMS M1139/M1144/M1145

MB 227.1

ZF TE-ML 06B/07B

Allison C4

Cat TO-2

Ford M2C134-D

John Deere J20C

Massey Ferguson CMS M1135/M1143

NH 410B

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,879
Viscosity -25 °C, mPa.s	4730
Viscosity 40 °C, mm ² /s	70,60
Viscosity 100 °C, mm ² /s	11,40
Viscosity Index	154
Flash Point COC, °C	228
Pour Point, °C	-33
Total Base Number, mgKOH/g	11,3
Sulphate Ash, %	1,57
Noack, %	12,7

Available packagings



34445
5 L can



32728
20 L Bag in
Box



35055
20 L pail



10072
20 L can



10132
60 L drum



34298
200 L drum



10236
208 L drum



35861
999 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.