

Product Information 01.20.11

06-05-2024

Kroon-Oil Bi-Turbo 20W-50

Description

Bi-Turbo 20W-50 is a universal, mineral motor oil based on premium solvent-refined base oils. It is supplemented with additives to achieve the following properties:

- Very powerful detergency and dispersion thereby preventing a high build-up of black sludge
- Very high resistance to oxidation
- Highly effective against wear
- Good resistance to corrosion and foaming
- A high and stable viscosity index
- A low tendency to evaporate
- No negative influence on catalytic converters

Application

Bi-Turbo 20W-50 is a universal mineral motor oil for petrol, diesel and LPG engines in cars and vans, whether or not fitted with an exhaust gas turbine or catalytic convertor. Always consult the Kroon-Oil advisory database for optimal use.

Specifications

ACEA A3/B4

API SL/CF

MB 229.1

VW 501.01/505.00

Typicals

Density at 15 °C, kg/l 0,896

Viscosity -15 °C, mPa.s 8190

Viscosity 40 °C, mm²/s 164,00

Viscosity 100 °C, mm²/s 17,60

Viscosity Index 120

Flash Point COC, °C 238

Pour Point, °C -24

Total Base Number, mgKOH/g 10,3

Sulphate Ash, % 1,29

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings



00221
1 L bottle



33079
4 L can



00340
5 L can



37489
15 L Bag in
Box



32902
20 L Bag in
Box



35063
20 L pail



35117
20 L can



10133
60 L drum



34752
200 L drum



10238
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.