

Product Information 02.20.40

02-05-2024

Kroon-Oil Syngear MT/LD 75W-80

Description

Syngear MT/LD 75W-80 is a fuel-saving, low-viscosity synthetic Long Life transmission oil. It is supplemented with state-of-the-art additives to achieve the following properties:

- Outstanding thermal stability, maintaining the low viscosity for a long time
- Very high resistance to rust, corrosion and foaming
- A low pour point, which ensures easy gear-changing at very low temperatures
- Premium 'Extreme Pressure' properties
- Long usability

Application

Syngear MT/LD 75W-80 has been specially developed for modern, heavy-duty (compact) and manual transmissions in which operating temperatures can reach very high levels. This product is also particularly suitable for when the manufacturers require long oil change intervals. Consult the product specifications in the product sheet for correct usage.

Specifications

API GL-4
MAN 341 Typ Z4
ZF TE-ML 01L / 02L / 16K
DAF
Eaton Europe (extended drain)
Iveco
Renault
Volvo 97307
ZF TE-ML 08 / 13 / 24A

Typicals

Density at 15 °C, kg/l	0,858
Viscosity 40 °C, mm²/s	59,50
Viscosity 100 °C, mm²/s	10,00
Viscosity Index	155
Flash Point COC, °C	218
Pour Point, °C	-39
Total Base Number, mgKOH/g	4,2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



32744 20 L Bag in Box

57018



20 L pail



12175 60 L drum



35131 20 L can

34553 200 L drum



12271 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.