Product Information 01.40.88

12-10-2024

Kroon-Oil Duranza ECO 5W-20

Description

Duranza ECO 5W-20 is fuel-saving, extremely modern, synthetic motor oil, specially developed for the new Ford EcoBoost petrol engines. The product has been developed in line with the latest technologies and is based on the latest generation of premium base oils with a naturally high viscosity index. It is supplemented with advanced additives to achieve the following properties:

- A very high level of fuel saving
- A very high and stable viscosity index
- Significant resistance to shearing
- A very smooth cold start, even at extremely low temperatures
- Protective lubricant film at extremely high operating temperatures
- Reduced formation of combustion residues
- Excellent dispersion and detergency
- Very high resistance to wear, corrosion and foaming

Application

Duranza ECO 5W-20 is an extremely low-viscosity, fuel-saving synthetic motor oil, specially developed for the new Ford EcoBoost petrol engines. Along with use in the new Ford EcoBoost engines, Duranza ECO 5W-20 can also be used when car manufacturers recommend ACEA A1/B1 or API SN quality SAE 5W-20 motor oil.

Specifications

ACEA C5
API SP
Ford WSS-M2C948-B
Jaguar Land Rover STJLR.03.5004

Typicals

Density at 15 °C, kg/l	0,852
Viscosity -30 °C, mPa.s	4380
Viscosity 40 °C, mm²/s	42,30
Viscosity 100 °C, mm²/s	8,23
Viscosity Index	160
Flash Point COC, °C	216
Pour Point, °C	-36
Total Base Number, mgKOH/g	8,8
Sulphate Ash, %	0,75

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com

Available packagings

35172	35173	37465	32900	35174	35175	35176	32169
1 L bottle	5 L can	15 L Bag in Box	20 L Bag in Box	20 L pail	60 L drum	208 L drum	1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com