

Product Information 05.10.10

23-04-2024

2T Super

Description

2T Super is a 2-stroke motor oil based on carefully selected premium base oils. It is supplemented with special, 2-stroke additives to achieve the following properties:

- The lubrication of all engine parts
- Powerful detergency, as a result of which the combustion chamber and the exhaust ports remain clear of deposits
- The spark plug remains clean, ensuring optimal performance of the engine
- Excellent resistance to corrosion and wear
- Limited smoke formation

Application

2T Super is particularly suitable for engines that operate under normal conditions. The product is also suitable for 2-stroke engines with water cooling, also known as radiator cooling. 2T Super is self-mixing and is used at a mixing ratio of 1 part oil to 50 parts fuel, or the mixing ratio required by the engine manufacturer.

Specifications

API TC

Typicals

Density at 15 °C, kg/l	0,880
Viscosity 40 °C, mm ² /s	67,40
Viscosity 100 °C, mm ² /s	9,50
Viscosity Index	115
Flash Point PM, °C	118
Flash Point COC, °C	152
Pour Point, °C	-18
Total Base Number, mgKOH/g	0,9
Sulphate Ash, %	0,09

Available packagings



00218
1 L bottle



35048
20 L pail



35215
20 L can



10119
60 L drum



10219
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.