

## Product Information 01.70.25

02-05-2024

### Running-In Monograde 30

#### Description

Running-In Monograde 30 is a special SAE 30 motor oil that has been specially developed for optimal and rapid running in of overhauled classic combustion engines and features the following properties:

- Ensures the correct and rapid running in of all moving parts in an overhauled engine
- Provides complete protection to the overhauled engine during the running-in process
- Ensures optimal sealing between the piston rings and cylinder wall once the overhaul is complete
- A well run-in engine will use a minimal amount of oil and will make the most economic use of fuel

#### Application

Running-In Monograde 30 is a mineral SAE 30 motor oil for optimal and rapid running-in of overhauled classic combustion engines. After overhauling, fill the engine with Running-In Monograde 30 and run the engine in for around 1000 km using a variety of driving styles and in a manner that achieves maximum torque. When driving, avoid maximum revs and maximum engine loads as far as possible. After the running-in period, replace the Running-In Monograde 30 with the recommended type of motor oil.

#### Specifications

API SE/CC

#### Typicals

Density at 15 °C, kg/l	0,892
Viscosity 40 °C, mm <sup>2</sup> /s	103,00
Viscosity 100 °C, mm <sup>2</sup> /s	11,70
Viscosity Index	98
Flash Point COC, °C	230
Pour Point, °C	-18
Total Base Number, mgKOH/g	3,5
Sulphate Ash, %	0,55

#### Available packagings



34542  
1 L tin



35323  
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.