



Product Information 01.20.65

26-04-2024

Dieselfleet MSP 10W-30

Description

Dieselfleet MSP 10W-30 is a diesel motor oil of the latest generation for use in the latest high-speed, heavy-duty 4-stroke diesel engines. Dieselfleet MSP 10W-30 is based on premium, solvent-refined base oils with unique high-quality Low SAPS additives. This multigrade motor oil features the following properties:

- Meets or exceeds the latest emission requirements
- Very powerful detergency: minimising deposits in the hot zone of the engine
- Very strong dispersion: deposits and sludge formation are severely restricted
- Very resistant to corrosion and foaming
- A high and stable viscosity index
- A low sulfate ash content
- Powerful wear resistance: resulting in reduced wear of piston rings and cylinder wall

Application

Dieselfleet MSP 10W-30 is a heavy-duty motor oil suitable for both on and off-road driving. Dieselfleet MSP 10W-30 contributes to low exhaust gas emissions and low particulate emissions, thereby extending the service-life of catalytic converters and particulate filters. The fact that this Low SAPS motor oil fulfils the requirements of truck manufacturers in Europe and North America alike, means that it can be used for a whole host of applications.

Specifications

ACEA E7, E9, E11

API CK-4

Mack EOS-4.5

Renault VI RLD-3

Volvo VDS-4.5

Cat ECF-3

Cummins CES 20086

Detroit Diesel 93K222

Deutz DQC III-18 LA

DTFR 15C100

Ford WSS M2C171-F1

MAN M 3775

MB 228.31

MTU Type 2.1

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Typicals

Density at 15 °C, kg/l	0,871
Viscosity -25 °C, mPa.s	6220
Viscosity 40 °C, mm ² /s	80,80
Viscosity 100 °C, mm ² /s	12,00
Viscosity Index	143
Flash Point COC, °C	230
Pour Point, °C	-42
Total Base Number, mgKOH/g	9,7
Sulphate Ash, %	0,99

Available packagings



35327
20 L pail



35328
60 L drum



35329
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.