

Product Information 01.10.21

19-06-2021

HDX 20W-20

Description

HDX 20W-20 is a single-grade motor oil based on premium solvent-refined base oils with additives to achieve the following properties:

- Powerful detergency and dispersion
- High resistance to oxidation
- High resistance to wear, corrosion and foaming

Application

HDX 20W-20 is a lubricant oil suitable for petrol engines along with diesel engines for cars and vans working under light conditions. Not suitable for turbo diesels that require a minimum of an API CD or Mil-L-2104 C/D level.

Specifications

API SF/CC

CCMC G2/D1

Typicals

Density at 15 °C, kg/l	0,876
Viscosity -15 °C, mPa.s	5000
Viscosity -10 °C, mPa.s	2400
Viscosity 40 °C, mm ² /s	68,00
Viscosity 100 °C, mm ² /s	8,00
Viscosity Index	98
Flash Point COC, °C	215
Pour Point, °C	-24
Total Base Number, mgKOH/g	3,5
Sulphate Ash, %	0,55

Available packagings



35043
20 L pail



10106
60 L drum



10206
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.