

## Product Information 08.60.36

19-06-2021

### Abacot FG 150

#### Description

Abacot FG 150 is a premium, transmission oil for the pharmaceutical and food industry. The product is based on a mix of specially selected, food-safe, white base oils and advanced additives, and features the following special properties:

- Resistant to high pressures and shock loads
- Can be used within a temperature range of -5 °C to 140 °C
- Effective against rust/corrosion
- Outstanding wear resistance
- Excellent resistance to foaming
- No coating and/or deposits are formed
- Non-toxic

#### Application

Abacot FG 150 is a food-safe transmission oil for use in the pharmaceutical and food industry, and is H1 registered. That is why Abacot FG 150 is particularly suitable for lubricating almost all types of industrial gear transmissions in which incidental contact between the lubricant and food might occur.

#### Specifications

DIN 51517-3 CLP

ISO 12925-1 CKB

#### Typicals

Density at 15 °C, kg/l	0,874
Viscosity 40 °C, mm <sup>2</sup> /s	143,60
Viscosity 100 °C, mm <sup>2</sup> /s	14,80
Viscosity Index	103
Flash Point COC, °C	250
Pour Point, °C	-9
Acid number, mgKOH/g	0,75
Demulsibility D1401	8'

#### Available packagings



35353

20 L can



35355

208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.