Product Information 08.60.19

25-04-2024

Heat Transfer Oil 32

Description

Heat Transfer Oil 32 is a heat transfer oil which consists of very carefully selected and refined base oils, which achieves the following properties:

- Good thermal stability
- Good oxidation stability
- Limited deposits in the installation
- Non-corrosive

Application

Heat Transfer Oil 32 is used as a heat transporting medium in closed circulation systems, working with indirect heating and high temperatures (above 100 °C). The system can be operated up to 300 °C without an inert gas. For temperatures between 300 and 320 °C, there must be a light overpressure from an inert gas.

Typicals

Density at 15 °C, kg/l	0,870
Viscosity 40 °C, mm²/s	32,00
Viscosity 100 °C, mm²/s	5,36
Viscosity Index	104
Flash Point COC, °C	224
Pour Point, °C	-15

Available packagings

57007
20 L pail

35419
20 L can

12145
60 L drum

35209
200 L drum

12243
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com