

Product Information 01.40.92

21-02-2019

Seal Tech 5W-30

Description

Seal Tech 5W-30 has been specially developed to provide protection for critical engine parts in vehicles with more than 120,000 km on the clock. This motor oil is based on special base oils, supplemented with, among others, life-extending seal agents and additives that encourage the reduction of sludge and deposits in the engine. As a result, the following properties will be achieved:

- Suitable for engines that have driven 120,000 km or more
- Delays the ageing process of the engine
- Improves protection against wear
- Improved oxidation stability
- Excellent cleaning ability
- Good cold start properties
- Minimises oil consumption
- Improves the condition of the gaskets and prevents oil leakage

Application

Seal Tech 5W-30 is suitable for use in petrol and diesel engines in cars and vans that have driven 120,000 km or more. The addition of special 'Seal Conditioners' prevents leaks in older engines and reduces oil consumption. This can have a positive effect on the ageing process and the protection of your engine.

Specifications

ACEA A3-98, B3-98

API SJ/CF

Typicals

Density at 15 °C, kg/l	0,857
Viscosity -30 °C, mPa.s	5900
Viscosity 40 °C, mm ² /s	67,60
Viscosity 100 °C, mm ² /s	11,40
Viscosity Index	163
Flash Point COC, °C	200
Pour Point, °C	-45
Total Base Number, mgKOH/g	8,2

Available packagings



35465
1 L bottle



35438
5 L can



35708
20 L pail



35493
60 L drum



35934
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.