



Product Information 01.40.93

28-01-2023

Poly Tech 5W-30

Description

Poly Tech 5W-30 is a premium motor oil that protects critical engine parts in vehicles operating under extreme conditions. The product is based on high-quality base oils combined with a highly advanced package of additives that includes special 'OSP' additives, among others. Poly Tech 5W-30 features the following properties:

- Vastly improved cleaning properties
- Outstanding shear stability thanks to the high VI of the base oils used
- A very smooth cold start, even at extremely low temperatures, significantly reducing wear on starting
- Delays the ageing process of the engine
- Excellent protection against wear and corrosion
- Improved oxidation stability
- Reduces friction in the moving engine parts
- Minimises oil consumption

Application

Poly Tech 5W-30 is suitable for use in both petrol and diesel engines in cars and vans. By using special 'OSP' additives, Poly Tech 5W-30 is ideally suited for use in vehicles exposed to extreme conditions. This may include frequently crawling through heavy traffic, 'sporty' driving or regular cold starts.

Specifications

ACEA C2, C3

API SN

BMW Longlife-04

GM dexos 2

MB 229.31 / 229.51 / 229.52

Opel OV 040 1547 - D30 / G30

VW 505.00 / 505.01

Typicals

Density at 15 °C, kg/l	0,862
Viscosity -30 °C, mPa.s	6200
Viscosity 40 °C, mm ² /s	70,4
Viscosity 100 °C, mm ² /s	12,20
Viscosity Index	178
Flash Point COC, °C	226
Pour Point, °C	-42
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,78

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.