



## Product Information 01.30.79

23-06-2018

### Armado Synth LSP Ultra 5W-30

#### Description

Armado Synth LSP Ultra 5W-30 is a top quality fuel economy diesel engine oil based on the latest additive technology combined with very special base oils. This engine oil has the following properties:

- Very powerful detergency prevents deposits in the engine
- Very strong dispersion that prevents from precipitation and sludge
- A powerful activity against wear, corrosion and foam
- A high and stable viscosity index
- A low sulphated ash number
- Prolonged oil drain intervals
- A lower fuel consumption

#### Application

Armado Synth LSP Ultra 5W-30 is a fuel-saving lubricant oil, specially developed for diesel engines that are used in the most severe operating conditions in all seasons. This product is highly suitable for use in EURO 4, EURO 5 and EURO 6 engines in combination with diesel fuels with a low sulfur content. This motor oil is also suitable for use in engines with or without particulate filters and catalytic converters. This motor oil is part of the Low SAPS group of lubricants.

#### Specifications

ACEA E6, E7, E9

API CJ-4/SN

MB-Approval 228.31/228.51

MAN M 3677/M 3477/M 3271-1

Volvo VDS-4/VDS-3

Scania Low Ash

Mack EO-O Premium Plus/EO-N

Renault VI RLD-3/RLD-2

Scania LDF-4

MTU Type 3.1

Mack EO-M Plus, Cummins CES 20081

Cat ECF-3, Detroit Diesel 93K218

Deutz DQC IV-10 LA, JASO DH-2

Voith class B

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Typicals**

Density at 15 °C, kg/l	0,855
Viscosity -30 °C, mPa.s	6460
Viscosity 40 °C, mm <sup>2</sup> /s	70,20
Viscosity 100 °C, mm <sup>2</sup> /s	11,80
Viscosity Index	165
Flash Point COC, °C	214
Pour Point, °C	-45
Total Base Number, mgKOH/g	9,3

**Available packagings**35621  
20 L pail35622  
60 L drum35623  
208 L drum