



Product Information 01.20.51

05-12-2023

Multifleet SHPD 10W-40

Description

Multifleet SHPD 10W-40 is a modern, universal motor oil based on premium solvent-refined base oils, supplemented with carefully balanced additives. Multifleet SHPD 10W-40 features the following properties:

- Excellent detergency, thereby preventing deposits in the hot zone of the engine
- Excellent dispersion, which acts to prevent the formation of sediment and sludge
- High resistance to wear, corrosion and foaming
- A high and stable viscosity index
- A low ash content

Application

Multifleet SHPD 10W-40 is a universal lubricant oil suitable for petrol and diesel engines both with and without turbochargers, under all operating conditions in all seasons. If extended oil change intervals (up to 30,000 km) are permitted by the engine manufacturers, this oil can also be used.

Specifications

ACEA A3/B4, E7

API CI-4 / SL

Cat ECF-1-a / ECF-2

Cummins CES 20077 / 20078

Deutz DQC III-18

DTFR 15B110

MAN M 3275

MB 228.3

MTU Type 2

Typicals

Density at 15 °C, kg/l	0,868
Viscosity -25 °C, mPa.s	4910
Viscosity 40 °C, mm ² /s	87,70
Viscosity 100 °C, mm ² /s	13,70
Viscosity Index	159
Flash Point COC, °C	222
Pour Point, °C	-36
Total Base Number, mgKOH/g	11,1
Sulphate Ash, %	1,43

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Available packagings



35036
20 L pail



10065
20 L can



10121
60 L drum



33857
200 L drum



10221
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.