



## Product Information 02.30.40

04-06-2023

### ATF Almirol

#### Description

ATF Almirol is a premium automatic transmission oil for the latest generation. By selecting premium-quality base oils and optimising the synthetic package of additives, the product features the following unique properties:

- Extremely low viscosity at low temperatures
- A very high and stable viscosity index
- A very low pour point
- Excellent oxidation stability at high temperatures
- Effective resistance to wear, corrosion and foaming
- Special friction properties
- Does not affect seals and non-ferrous metals

#### Application

ATF Almirol is suitable for automatic transmissions, power steering systems, torque converters and other applications for which General Motors and other constructors recommend a type ATF Dexron III-H oil. Consult the product specifications in the product sheet for correct usage.

#### Specifications

Allison C4/TES-389

Cat TO-2

Ford Mercon/M2C138-CJ/166-H

GM Dexron IID/IIE/IIIF/IIIG/IIIH

MAN 339 Typ Z1/V1

MB 236.1/236.5/236.6/236.7/236.9

Voith 55.6335 (G607)

Volvo 97341

ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

#### Typicals

Density at 15 °C, kg/l 0,854

Viscosity 40 °C, mm<sup>2</sup>/s 35,80

Viscosity 100 °C, mm<sup>2</sup>/s 7,30

Viscosity Index 175

Flash Point COC, °C 226

Pour Point, °C -51

Total Base Number, mgKOH/g 0,9

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Available packagings**



01212  
1 L bottle



01322  
5 L can



32740  
20 L Bag in  
Box



36087  
20 L pail



11175  
60 L drum



11275  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.