

Product Information 02.10.32

01-05-2024

Gearlube RPC 75W-80

Description

Gearlube RPC 75W-80 is a premium transmission oil based on solvent-refined base oils. By using selected mineral base oils and special additives, the following properties are achieved:

- Excellent resistance to wear
- Excellent resistance to corrosion
- Excellent oxidation stability
- Good resistance to foaming
- Low viscosity at low temperatures
- A very high and stable viscosity index

Application

Gearlube RPC 75W-80 has been specially developed for use in a range of manual transmissions in French makes of car, such as Renault, Peugeot and Citroën. Gearlube RPC 75W-80 can be used in cases in which an API GL-5 Renault or an API GL-5 PSA specification is required. It can also be used when the manufacturer recommends a low-viscosity transmission oil.

Specifications

API GL-4+

MIL-L-2105

PSA B71 2330

Typicals

Density at 15 °C, kg/l	0,848
Viscosity 40 °C, mm ² /s	49,30
Viscosity 100 °C, mm ² /s	9,15
Viscosity Index	170
Flash Point COC, °C	220
Pour Point, °C	-39
Total Base Number, mgKOH/g	8,7
Acid number, mgKOH/g	1,34
Sulphate Ash, %	1,34

Available packagings



01210
1 L bottle



32746
20 L Bag in
Box



36089
20 L pail



35375
20 L can



11160
60 L drum



11260
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.