

Product Information 01.20.52

26-04-2024

Kroon-Oil Multifleet SHPD 20W-50

Description

Multifleet SHPD 20W-50 is a modern, universal motor oil based on premium solvent-refined base oils, supplemented with carefully balanced additives. Multifleet SHPD 20W-50 features the following properties:

- Excellent detergency, thereby preventing deposits in the hot zone of the engine
- Excellent dispersion, which acts to prevent formation of sediment and sludge
- Very high resistance to wear, corrosion and foaming
- A high and stable viscosity index
- A low ash content

Application

Multifleet SHPD 20W-50 is a universal lubricant oil suitable for petrol and diesel engines with and without turbochargers. The product can be used in all seasons, under all operating conditions. Multifleet SHPD 20W-50 can also be used whenever extended oil change intervals (up to 30,000 km) are permitted by the engine manufacturers.

Specifications

ACEA E7

API CH-4/SJ

Deutz DQC III-10

MB 228.1

Typicals

| | |
|--------------------------------------|--------|
| Density at 15 °C, kg/l | 0,894 |
| Viscosity -15 °C, mPa.s | 7600 |
| Viscosity 40 °C, mm ² /s | 154,30 |
| Viscosity 100 °C, mm ² /s | 17,30 |
| Viscosity Index | 122 |
| Flash Point COC, °C | 226 |
| Pour Point, °C | -30 |
| Total Base Number, mgKOH/g | 11,1 |
| Sulphate Ash, % | 1,43 |

Available packagings



00332
5 L can



37528
15 L Bag in
Box



35037
20 L pail



31077
20 L can



10124
60 L drum



31339
200 L drum



34466
200 L drum



10224
208 L drum



34579
1000 L IBC

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.