

## Product Information 08.50.07

03-05-2024

### Kroon-Oil Paraflo 15

#### Description

Paraflo 15 is a white, technical mineral oil. The product is mainly made up of a mixture of saturated paraffin and cycloparaffin hydrocarbons. As a result of intensive refining, this oil is acid-free and almost colour and odour-free.

#### Application

Paraflo 15 is used:

- As a lubricant for precision engineering equipment and for sewing machines and other textile machines
- As a raw material for various processes PLEASE NOTE! This oil should not be used in the medical and food industries, in which food products may come into contact with the oil.

#### Typicals

|                                      |       |
|--------------------------------------|-------|
| Density at 15 °C, kg/l               | 0,852 |
| Viscosity 20 °C, mm <sup>2</sup> /s  | 37,50 |
| Viscosity 40 °C, mm <sup>2</sup> /s  | 15,60 |
| Viscosity 100 °C, mm <sup>2</sup> /s | 3,60  |
| Viscosity Index                      | 114   |
| Flash Point PM, °C                   | 183   |
| Flash Point COC, °C                  | 192   |
| Pour Point, °C                       | -21   |

#### Available packagings



02216  
1 L bottle



37000  
20 L pail



35418  
20 L can



12142  
60 L drum



35417  
200 L drum



12240  
208 L drum



34804  
1000 L IBC