

Product Information 08.20.03 28-04-2024

Kroon-Oil Pneumolube

Description

Pneumolube is the perfect lubricant for tools driven on compressed air. Pneumolube is based on a water-soluble synthetic lubricant, supplemented with specific additives to achieve the following properties:

- Good resistance to corrosion, oxidation and wear
- Prevents the formation of ice deposits in compressed air tools and machines
- Prevents the formation of deposits in the pneumatic system
- Mild cleaning effect
- Does not affect rubber and/or synthetic parts

Application

Pneumolube is used as a mist lubricant for pneumatic systems such as: demolition hammers, drills, air motors and pneumatic hammers. The product does not mix with other mineral products, but cleaning the systems is not required. Work can still take place down to -25 °C without the pneumatic system freezing.

Typicals

Density at 15 °C, kg/l	1,102
Viscosity 20 °C, mm ² /s	23,00
Viscosity 40 °C, mm²/s	10,00
Pour Point, °C	-75
Refraction Index 20°C	1,417
pH - 10 % in water	8,5

Available packagings









1 L bottle

20 L pail

12109 60 L drum

12207 208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.