

Product Information 08.60.06

27-07-2024

Carsinus VAC 220

Description

Carsinus VAC 220 is a vacuum pump oil, based on specially selected solvent-refined base oils. It is supplemented with additives to achieve the following properties:

- Outstanding wear resistance
- Excellent rust and corrosion protection
- Excellent oxidation stability
- Excellent demulsifier
- Excellent air-release and resistance to foaming
- Does not affect synthetic seals
- A low pour point

Application

Carsinus VAC 220 is suitable for lubricating vacuum pumps, for both crankcase and mist lubrication, where at least an HLP oil is recommended.

Specifications

AFNOR NF E 48-603 HM

ASTM D 6158 HM

DIN 51524-2 HLP

ISO 11158 HM

Typicals

Density at 15 °C, kg/l	0,897
Viscosity 40 °C, mm ² /s	220,00
Viscosity 100 °C, mm ² /s	18,80
Viscosity Index	95
Flash Point COC, °C	246
Pour Point, °C	-18
Acid number, mgKOH/g	0,40
Sulphate Ash, %	0,06

Available packagings



37094
20 L pail



12120
60 L drum



12218
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.