

Product Information 07.30.01

19-04-2024

Kroon-Oil Compound OGL

Description

Compound OGL is a special compound formulated from highly refined mineral base oils with solvents. It is supplemented with special Bitumen 'Extreme Pressure' and wear-reducing molybdenum additives to achieve the following properties:

- Effective protection against wear under heavy loads
- Excellent penetrative ability that even enables it to reach steel wire cable cores
- Excellent water-resistance in both fresh and salt water environments
- Effective protection against corrosion
- Excellent adhesion to metals
- Also remains flexible at very low temperatures down to approx. -35 °C

Application

Compound OGL is used as a lubricant for heavy-duty open gears. Some examples are: turntables, drive chains that work in the open air or in a dusty environment and steel cables that need to be lubricated with a highly penetrating product that has effective protection against corrosion.

Specifications

N.L.G.I. klasse 0,5

DIN 51825, KPG0G0,5N-30

Typicals

4-ball welding load, N 7500

Available packagings



38001

400 ml aerosol

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.