

Product Information 07.10.25

20-05-2024

PTFE White Grease EP2

Description

PTFE White Grease EP 2 is a multipurpose grease based on highly refined, highly viscous base oils, which uses lithium-complex soap as a thickening agent, supplemented with additives to achieve the following properties:

- Strong adhesion to metal
- Outstanding water displacement
- Excellent stability
- Effective resistance to corrosion and wear
- Excellent pumpability

Application

PTFE White Grease EP 2 can be used for the lubrication of bearings in the road traffic, industrial and shipping sectors. PTFE White Grease EP 2 is suitable for lubrication points that could otherwise result in dirty stains if in contact with clothing, such as window and switching mechanisms, hinges, springs, locks, etc.

Specifications

NLGI Grade 2

DIN 51502: KPF2N-30

ISO 12924: L-XC(F)DIB2

Typicals

Dropping Point, °C	270
Temperature Limits, °C	-30/140
Base oil Viscosity, 40 °C, mm ² /s	210,00
4-ball welding load, N	3000

Available packagings



13402

400 g cartridge



34076

600 g pot



38041

18 kg pail

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.