

## Product Information 98.40.01 28-04-2024

# Gear Oil Alcat 30

### Description

Gear Oil Alcat 30 is a special oil for hydraulic and transmission applications, based on solvent-refined base oils and supplemented with additives to achieve the following properties:

- A very low pour point
- Excellent oxidation stability
- Good wear resistance, as a result of which the final drives achieve a longer service life
- Special friction properties that ensure optimal use of powershift transmissions
- Suitable for systems with wet brakes
- Outstanding resistance to rust and corrosion

#### Application

Gear Oil Alcat 30 has been specially developed for the lubrication of powershift transmissions, differentials, final drives and hydraulic systems in earth moving equipment for which oil is recommended that complies with the Caterpillar TO-4 or Allison C4 specifications.

THE OIL CANNOT BE USED IN ENGINES !!!

#### Specifications

API GL-4
Allison C4
Cat TO-4 / TO-2
Komatsu KES 07.868.1
ZF TE-ML 03C / 07D / 07F
Eaton (Vickers) M-2950-S / I-286-S

### Typicals

Density at 15 °C, kg/l	0,897
Viscosity 40 °C, mm²/s	95,60
Viscosity 100 °C, mm²/s	11,00
Viscosity Index	100
Flash Point COC, °C	238
Pour Point, °C	-30
Total Base Number, mgKOH/g	9,5
Sulphate Ash, %	1,32
HTHS, mPa.s	3,27

## Available packagings

		**Rappa de *	a mangeme des l'
56022	35770	31131	11279
20 L pail	20 L can	60 L drum	208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Kroon-Oil B.V. Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@kroon-oil.com