Product Information 02.20.20

29-04-2024

Gearlube HS GL-5 75W-90

Description

Gearlube HS GL-5 75W-90 is an extremely modern synthetic transmission oil. By using low-viscosity, synthetic base oils combined with advanced additives, the following properties are achieved:

- Saves fuel (cost benefit)
- Does not affect seals in any way (no risk of leakage)
- A strong lubricant film, even under the toughest conditions (high technical reliability)
- Its low viscosity ensures that gear-changing takes place more easily (ease of use)
- Effectively prevents wear on the gearbox and bearings (extending the service life of drive line)
- Copes exceptionally well with the (extended) oil change intervals that apply nowadays (for added security)

Application

Gearlube HS GL-5 75W-90 is a fuel-saving synthetic transmission oil and has been developed for use in the most heavy-duty hypoid transmissions in rear axles and manual transmissions. It can also be used in all transmissions in which 'Extreme Pressure' oils are recommended.

Specifications

API GL-5
MIL-L-2105D
ZF TE-ML 07A/17B

Typicals

Density at 15 °C, kg/l	0,872
Viscosity 40 °C, mm²/s	80,90
Viscosity 100 °C, mm²/s	14,80
Viscosity Index	192
Flash Point COC, °C	190
Pour Point, °C	-45

Available packagings

37508	57015	35077	12173	34356	12269
15 L Bag in Box	20 L pail	20 L can	60 L drum	200 L drum	208 L drum