

Product Information 01.40.82 07-05-2024

Expulsa RR 5W-40

Description

Expulsa RR 5W-40 is a fully synthetic, superior performance 4-stroke engine oil for the latest generation of motorcycles. The product is based on premium synthetic base oils and special, advanced additives to achieve the following properties:

- Outstanding protection against wear even at extremely high or low temperatures
- Excellent lubrication under the most extreme operating conditions
- Low volatility, therefore resulting in minimal oil consumption
- Very limited internal friction for maximum engine performance
- A very high and stable viscosity index
- Outstanding cleaning properties, ensuring that the interior of the engine remains clean
- Ensures that gear-changing is both smooth and accurate
- Optimally functioning wet clutch

Application

Expulsa RR 5W-40 has been developed specifically for modern, high-tech, high to very high-powered motorcycles. This fully synthetic formula means that Expulsa RR 5W-40 offers superior lubrication, even at extremely high operating temperatures. This makes the product particularly suitable for use in sports and on the circuit, as well as when riding on normal roads.

Specifications

API SN		
JASO MA2		

Typicals

Density at 15 °C, kg/l	0,842
Viscosity -35 °C, mPa.s	5500
Viscosity -30 °C, mPa.s	3270
Viscosity 40 °C, mm²/s	82,00
Viscosity 100 °C, mm²/s	13,80
Viscosity Index	173
Flash Point COC, °C	232
Pour Point, °C	-60
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,85

Available packagings

		**XRQUA dit *	
33016	58036	33037	32670
1 L bottle	20 L pail	60 L drum	208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.