

## Product Information 01.40.81

24-04-2024

### Expulsa RR 10W-40

#### Description

Expulsa RR 10W-40 is a fully synthetic, superior performance 4-stroke engine oil for the latest generation of motorcycles. The product has been formulated using premium, synthetic base oils, combined with special, advanced additives. The product has the following properties:

- Outstanding protection against wear even at extremely high or low temperatures
- Excellent lubrication under the most extreme operating conditions
- A low volatility, therefore resulting in minimal oil consumption
- Very limited internal friction for maximum engine performance
- A very high and stable viscosity index
- Outstanding cleaning properties, ensuring that the interior of the engine remains clean
- Ensures that gear-changing is both smooth and accurate
- Optimally functioning wet clutch

#### Application

Expulsa RR 10W-40 has been developed specifically for modern, high-tech, high to very high-powered motorcycles. This fully synthetic formula means that the product offers superior lubrication, even under extremely high operating temperatures. This makes Expulsa RR 10W-40 particularly suitable for use in sports and on the circuit, as well as when riding on normal roads.

#### Specifications

API SN

JASO MA2

#### Typicals

Density at 15 °C, kg/l	0,842
Viscosity -25 °C, mPa.s	2320
Viscosity 40 °C, mm <sup>2</sup> /s	83,40
Viscosity 100 °C, mm <sup>2</sup> /s	14,00
Viscosity Index	166
Flash Point COC, °C	221
Pour Point, °C	-60
Total Base Number, mgKOH/g	7,7
Sulphate Ash, %	0,85

#### Available packagings



33014  
1 L bottle



58040  
20 L pail



33041  
60 L drum



32672  
208 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.