

## Product Information PG.30.00

18-09-2019

### ATF

#### Description

ATF is a premium-grade transmission oil with the following properties:

- Good friction reduction properties
- High oxidation and thermal stability
- Guarantees a long service life ATF is suitable for 2-stroke automatic and synchromesh gearboxes, powershift transmissions, torque converters, servo systems and hydraulic clutches.

#### Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

#### Specifications

GM Dexron IID/IIE/IIIF/IIIG/IIIH

#### Typicals

Density at 15 °C, kg/l	0,851
Viscosity 40 °C, mm <sup>2</sup> /s	37,70
Viscosity 100 °C, mm <sup>2</sup> /s	7,60
Viscosity Index	175
Flash Point COC, °C	210
Pour Point, °C	-51
Total Base Number, mgKOH/g	1,9

#### Available packagings



70021  
1 L bottle



74427  
20 L Bag in  
Box



70023  
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.