

Product Information PC.10.00 03-07-2024

Putoline Coolant NF

Description

Coolant NF is a ready-to-use, organic coolant. Anti-corrosion additives provide excellent protection for all metals found in engines, including aluminium and magnesium. The product provides frost protection down to -38°C.

Coolant NF is suitable for all Off Road and Road motorcycles, quads, scooters, karts and snowmobiles.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Typicals		
Density at 15 °C, kg/l	1,080	
Flash Point COC, °C	111	
Available packagings		
Available packagings		



70055 70057 1 L bottle 4 L can



74288 20 L Bag in

Box



70058

60 L drum

200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.