

Product Information PG.10.00

26-04-2024

Gear Heavy

Description

Heavy Gear is a special transmission oil with Extreme Pressure additives. The product is recommended for universal drives for which SAE 80W-90 is specified.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API GL-5

MIL-L-2105D

ZF TE-ML 16B / 17B / 19B / 21A

DTFR 12B100

Typicals

| | |
|--------------------------------------|--------|
| Density at 15 °C, kg/l | 0,898 |
| Viscosity 40 °C, mm ² /s | 149,00 |
| Viscosity 100 °C, mm ² /s | 14,80 |
| Viscosity Index | 98 |
| Flash Point COC, °C | 232 |
| Pour Point, °C | -30 |
| Acid number, mgKOH/g | 1,80 |
| Sulphate Ash, % | 0,05 |
| Brookfield -26°C, mPa.s | 290000 |

Available packagings



70148
1 L bottle



74297
20 L Bag in
Box



70153
60 L drum



70149
200 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.