Product Information PG.10.02

24-04-2024

Gear Medium

Description

Medium Gear is a modern transmission oil. The product provides outstanding protection when used in warmer climates. At ambient temperatures above 20°C the product reduces friction, delivering maximum power to the back wheel. Medium Gear is suitable for road and circuit use.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API GL-1

Typicals

Density at 15 °C, kg/l	0,893
Viscosity 40 °C, mm²/s	102,00
Viscosity 100 °C, mm²/s	11,50
Viscosity Index	98
Flash Point COC, °C	244
Pour Point, °C	-18
Sulphate Ash, %	0,15

Available packagings

70158
1 L bottle

74428
20 L Bag in Box

70161
60 L drum

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Putoline Dollegoorweg 15 7602 EC Almelo Phone +31 (0)546-818165. Sales +31 (0)546-816184. Fax +31 (0)546-817367. E-mail sales@putoline.com