

# **Product Information PG.20.00** 25-04-2024

# **GP 10**

#### Description

GP 10 is a modern gearbox oil. The product guarantees a significant reduction in friction and heat generation and this provides maximum power delivery to the rear wheel. GP 10 has been specifically developed for use on the circuit but can also be used very effectively in road bikes.

### **Application**

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

### **Specifications**

API GL-4

# **Typicals**

Density at 15 °C, kg/l	0,856
Viscosity 40 °C, mm²/s	33,50
Viscosity 100 °C, mm²/s	5,50
Viscosity Index	98
Flash Point COC, °C	205
Pour Point, °C	-39

# **Available packagings**







1 L bottle

20 L Bag in

60 L drum

Box

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.